

CRPQ-045E-PFV

HFC, R-407C, 60 Hz, 1 - Phase, 208/230 V

Air Conditioning

Production Status: Preliminary data only - Contact your Emerson Climate Technologies Representative.

Summary

Performance		
Evaporator Temp. (°F)	45	45
Condensing Temp. (°F)	130	100
Return Gas Temp. (°F)	65	65
Liquid Temp. (°F)	115	85
Capacity (BTU/hr)	54500	71200
Power (W):	5540	4700
Current (Amps):	25.3	21.7
EER(BTU/Wh):	9.85	15.15
Mass Flow (lbs/hr):	790	885
Sound Data @		
Sound Power (dBA):	79 Avg	84 Max
Vibration mils(peak-peak):	5.0 Avg	6.0 Max
Record Date:	2010-09-14	
Mechanical		
Displacement (in^3/Rev):	5.82	
Displacement (ft^3/Hr):		
Overall Length (in):	11.38	
Overall Width (in):	9.38	
Overall Height (in):	15.88	
Mounting Length (in):	7.50	
Mounting Width (in):	7.50	
Mounting Height (in):	16.25	

Suction Size (in),Type:	7 / 8 Stub
Discharge Size (in),Type:	1 / 2 Stub
Initial Oil Charge (oz):	70
Oil Recharge (oz):	66
Net Weight (lbs):	87.0
Internal Free Volume (in^3):	
Horse Power:	

*Overall compressor height on Copeland Brand Product's specified mounting grommets.

Electrical

LRA High* (Amps):	
LRA Low*(Amps):	
LRA Half Winding (Amps):	
MCC (Amps):	
Max Operating Current (Amps):	
RLA, MCC/1.4(use for contactor selection)(Amps):	1.0
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	
RPM:	3500
Box IP :	
UL File No:	
UL File Date:	1984-12-28

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Capacitors

Type	Part No	Low MFD	High MFD	Volts	User Description
Run Capacitor	014-0064-15	45.0	0.0	440	
Start Capacitor	014-0006-13	189.0	227.0	330	HIGH TORQUE

Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
R-407C HFC	200	1	50	Air Conditioning

Service Parts				
Reference	Component	Quantity	Description	Comment
99	521-0191-00	1	TERMINAL-SCREW GROUP	
99	521-0192-00	1	TERMINAL KIT	
99	527-0116-00	1	SPACER-MOUNTING ASSM	
99	914-0006-03	1	CAP START KIT	
99	914-0037-19	1	RUN CAP KIT	
99	918-0088-04	1	HEATER-CRANKCASE KIT	45/55W 240/265V FLEXIBLE
99	921-0227-00	1	CONNECTOR BLOCK KIT	
99	940-0001-68	1	RELAY KIT	

Electrical Components

Electrical Components

Part No: 071-0508-09

Usage Description: Internal Protector

Vendor Part Number

15HM1614

Vendor Name

T I

Potential

Part No: 040-0166-27

Usage Description: Potential Relay

Vendor Part Number

RVA4AL6D-930

Vendor Name

ELECTRICA

Run Capacitor

Part No: 014-0064-15

Low MFD: 45.0

Type:Run Capacitor

High MFD: 0.0

Usage Description: Run Capacitor

Volts: 440

Stator

Part No: 546-5072-00

Usage Description: Stator

Resistance: +/-7%

Start Wdg: 1.33

Run Wdg: 0.41

Start Capacitor

Part No: 014-0006-13

Low MFD: 189.0

Type:Start Capacitor

High MFD: 227.0

Usage Description: Start Capacitor

Volts: 330

Nomenclature

Family Series

C: CR Compressors

Application Range

R: R-22/ High Temp. A/C & Heat Pump

Capacity

: Capacity

Oil Type

: --

Motor Type

P: 1 Phase/Capacitor Run, Permanent Split Capacitor

Motor Protection

F: Internal Inherent Protection

Voltage

V: 60Hz (208/230-1) 50Hz (200-1)

Miscellaneous

Alternate Application				
Refrigerant	Freq	Phase	Voltage	Application
CFC R-502	50	1 Ø	200 V	R2
CFC R-502	60	1 Ø	208/230 V	R2
HCFC R-22	50	1 Ø	200 V	R1
HCFC R-22	60	1 Ø	208/230 V	R1
HFC R-407C	50	1 Ø	200 V	AC
Nomenclature				
CRPQ-045E-PFV				
Date	Data Group	Field	Old Data	New Data
14-Sep-2010	Rating	PubCode		PRE