

CRPQ-045E-TFD

HCFC, R-22, 60 Hz, 3 - Phase, 380/460 V [Also Available with Variable Frequency Drives](#)

Air Conditioning

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Summary

Performance		
Evaporator Temp. (°F)	45	45
Condensing Temp. (°F)	130	100
Return Gas Temp. (°F)	65	65
Liquid Temp. (°F)	115	85
Capacity (BTU/hr)	57000	72000
Power (W):	5650	4490
Current (Amps):	8	6.6
EER(BTU/Wh):	10.1	16.1
Mass Flow (lbs/hr):	835	930
Sound Data @		
Sound Power (dBA):	79 Avg	84 Max
Vibration mils(peak-peak):	5.0 Avg	6.0 Max
Record Date:	2014-03-06	
Mechanical		
Displacement (in^3/Rev):	5.82	
Displacement (ft^3/Hr):		
Overall Length (in):	11.38	
Overall Width (in):	9.38	
Overall Height (in):	15.88	
Mounting Length (in):	7.50	
Mounting Width (in):	7.50	

Mounting Height (in):	16.25
Suction Size (in),Type:	7 / 8 Stub
Discharge Size (in),Type:	1 / 2 Stub
Initial Oil Charge (oz):	70
Oil Recharge (oz):	66
Net Weight (lbs):	91.0
Internal Free Volume (in^3):	
Horse Power:	

*Overall compressor height on Copeland Brand Product's specified mounting grommets.

LRA High* (Amps):	55.0
LRA Low*(Amps):	
LRA Half Winding (Amps):	
MCC (Amps):	14.6
Max Operating Current (Amps):	
RLA, MCC/1.4(use for contactor selection)(Amps):	10.4
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	9.4
RPM:	
Box IP :	
UL File No:	
UL File Date:	1984-12-28

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Capacitors

Type	Part No	Low MFD	High MFD	Volts	User Description
No data available in table					

Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
R-22 HCFC	380/420	3	50	Air Conditioning
R-22 HCFC	380/420	3	50	High Temp
R-22 HCFC	380/460	3	60	High Temp
R-407C HFC		3	60	Air Conditioning

Refrigerant	Voltage	Phase	Frequency	Application
R-407C HFC		3	50	Air Conditioning
R-407C HFC		3	60	Air Conditioning

Service Parts

Service Parts				
Reference	Component	Quantity	Description	Comment
99	521-0191-00	1	TERMINAL-SCREW GROUP	
99	521-0192-00	1	TERMINAL KIT	
99	527-0116-00	1	SPACER-MOUNTING ASSM	
99	918-0088-05	1	HEATER-CRANKCASE KIT	45/65W 480V FLEXIBLE
99	921-0227-00	1	CONNECTOR BLOCK KIT	

Accessories

Accessories		
Category	Part Number	Description
(1) Variable Frequency Drive	EVH-344012-R54BDB	EVH, 3Ø, 380-480v, Output 380-480v@11A, LCD Keypad, IP54, With 5% DC Link Choke, With Bypass, Frame H3X

Electrical Components

Electrical Components

Part No: 071-0428-02

Usage Description: Internal Protector

Vendor Part Number

32HM050-6

Vendor Name

T I

Part No: 071-0526-03

Usage Description: Internal Protector

Vendor Part Number

35HM219-12

Vendor Name

T I

Stator

Part No: 046-5044-08

Usage Description: Stator

Resistance: +/-7%

Start Wdg: 2.83

Run Wdg: 0.00

Stator

Part No: 046-3088-05

Usage Description: Stator

Resistance: +/-7%

Start Wdg: 2.83

Run Wdg: 0.00

Stator

Part No: 046-5044-15

Usage Description: Stator

Resistance: +/-7%

Start Wdg: 2.83

Run Wdg: 0.00

Nomenclature

CRPQ-045E-TFD

Family Series

C: CR Compressors

Application Range

R: R-22/ High Temp. A/C & Heat Pump

Capacity

: Capacity

Oil Type

: --

Motor Type

T: 3 Phase

Motor Protection

F: Internal Inherent Protection

Voltage

D: 60Hz (460-3) 50Hz (380/420-3)

Miscellaneous

Alternate Application

Refrigerant	Freq	Phase	Voltage	Application
CFC R-502	50	3 Ø	380/420 V	R2 R2
CFC R-502	60	3 Ø	380/460 V	R2
HCFC R-22	50	3 Ø	380/420 V	R1 AC
HCFC R-22	50	3 Ø	380/420 V	R1 HT
HCFC R-22	60	3 Ø	380/460 V	R1 HT
HFC R-407C	60	3 Ø	V	AC
HFC R-407C	50	3 Ø	V	AC
HFC R-407C	60	3 Ø	V	AC

Nomenclature

[CRPQ-045E-TFD](#)

Date	Data Group	Field	Old Data	New Data
14-Jan-2014	Sound	Vibration Ave	2	5
14-Jan-2014	Sound	Vibration Max	3	6
05-Jun-2014	2 Pt Perf	MassFlow Cond 1	860	865
05-Jun-2014	2 Pt Perf	MassFlow Cond 2	464	466
06-Mar-2014	2 Pt Perf	Cap Cond 2	72100	72000
06-Mar-2014	2 Pt Perf	Watts Cond 1	5640	5650