

CR22K6E-PFJ

HCFC, R-22, 60 Hz, 1 - Phase, 265 V [.Also Available with Variable Frequency Drives](#)

Air Conditioning

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Summary

Performance		
Evaporator Temp. (°F)	45	45
Condensing Temp. (°F)	130	100
Return Gas Temp. (°F)	65	65
Liquid Temp. (°F)	115	85
Capacity (BTU/hr)	22100	29500
Power (W):	2040	1670
Current (Amps):	8	6.6
EER(BTU/Wh):	10.8	17.7
Mass Flow (lbs/hr):	323	380
Sound Data @		
Sound Power (dBA):	72 Avg	77 Max
Vibration mils(peak-peak):	1.9 Avg	2.9 Max
Record Date:		
Mechanical		
Displacement (in³/Rev):	2.49	
Displacement (ft³/Hr):		
Overall Length (in):	10.23	
Overall Width (in):	9.65	
Overall Height (in):	13.31	
Mounting Length (in):	7.50	
Mounting Width (in):	7.50	

Mounting Height (in):	13.69
Suction Size (in),Type:	3 / 4 Stub
Discharge Size (in),Type:	1 / 2 Stub
Initial Oil Charge (oz):	45
Oil Recharge (oz):	43
Net Weight (lbs):	62.0
Internal Free Volume (in³):	
Horse Power:	

*Overall compressor height on Copeland Brand Product's specified mounting grommets.

LRA High* (Amps):	55.0
LRA Low*(Amps):	
LRA Half Winding (Amps):	
MCC (Amps):	13.8
Max Operating Current (Amps):	
RLA, MCC/1.4(use for contactor selection)(Amps):	9.9
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	8.8
RPM:	
Box IP :	
UL File No:	
UL File Date:	1984-12-28

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Capacitors

Type	Part No	Low MFD	High MFD	Volts	User Description
Run Capacitor	014-0064-06	30.0	0.0	370	
Run Capacitor	014-0064-12	30.0	0.0	440	
Start Capacitor	014-0061-16	43.0	52.0	330	LOW TORQUE
Start Capacitor	014-0061-30	130.0	156.0	330	HIGH TORQUE

Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
R-404A HFC	220/240	1	50	High Temp

Refrigerant	Voltage	Phase	Frequency	Application
R-407C HFC	265	1	60	Air Conditioning

Service Parts

Service Parts				
Reference	Component	Quantity	Description	Comment
1	527-0044-00	1	SPACER-MOUNTING ASSM	
2	914-0036-07	1	CAP START KIT	
3	914-0037-16	1	RUN CAP KIT W/CLAMP	
4	940-0001-55	1	RELAY-POTENTIAL KIT	
10	918-0088-00	1	HEATER-CRANKCASE KIT	40/49W 240/265V FLEXIBLE
14	529-0060-24	1	POWER CABLE-MOLDED PLUG	
99	005-1210-00	1	COVER-TERMINAL BOX	

Accessories

Accessories		
Category	Part Number	Description
(1) Variable Frequency Drive	EVM-322011-E20ENN	EVM, 3Ø, 200-240v, Output 200-240v@11A, Pro, IP20, Standard, No Options, Frame 1
(1) Variable Frequency Drive	EVM-122011-E20ENN	EVM, 1Ø, 200-240v, Output 200-240v@11A, Pro, IP20, Standard, No Options, Frame 2
(1) Variable Frequency Drive	EVM-322011-N20MNN	EVM, 3Ø, 200-240v, Output 200-240v@11A, Basic, IP20, Standard, No Options, Frame 1
(1) Variable Frequency Drive	EVM-322011-N20MFN	EVM, 3Ø, 200-240v, Output 200-240v@11A, Basic, IP20, With add on EMI filter, No Options, Frame 1
(1) Variable Frequency Drive	EVM-322011-E20EFN	EVM, 3Ø, 200-240v, Output 200-240v@11A, Pro, IP20, With add on EMI filter, No Options, Frame 1
(1) Variable Frequency Drive	EVM-122011-E20EFN	EVM, 1Ø, 200-240v, Output 200-240v@11A, Pro, IP20, With add on EMI filter, No Options, Frame 2
(1) Variable Frequency Drive	EVH-322011-R21BDN	EVH, 3Ø, 200-240v, Output 200-240v@11A, LCD Keypad, IP21, With 5% DC Link Choke, No Options, Frame 1

Category	Part Number	Description
(1) Variable Frequency Drive	EVH-322011-R21BEN	EVH, 3Ø, 200-240v, Output 200-240v@11A, LCD Keypad, IP21, With 5% DC Link Choke + EMI Filter, No Options, Frame 1
(1) Variable Frequency Drive	EVH-322011-R54BDN	EVH, 3Ø, 200-240v, Output 200-240v@11A, LCD Keypad, IP54, With 5% DC Link Choke, No Options, Frame 1

Electrical Components

Electrical Components	
Part No: 071-0508-50	Stator
Usage Description: Internal Protector	Part No: 546-5081-11
<u>Vendor Part Number</u>	Usage Description: Stator
15HM1439	Resistance: +/-7%
<u>Vendor Name</u>	Start Wdg: 3.81
T I	Run Wdg: 1.33
Potential	Start Capacitor
Part No: 040-0166-15	Part No: 014-0061-16
Usage Description: Potential Relay	Low MFD: 43.0
<u>Vendor Part Number</u>	Type:Start Capacitor
RVA3AG6D-917	High MFD: 52.0
<u>Vendor Name</u>	Usage Description: Start Capacitor
ELECTRICA	Volts: 330
Start Capacitor	Run Capacitor
Part No: 014-0061-30	Part No: 014-0064-06
Low MFD: 130.0	Low MFD: 30.0
Type:Start Capacitor	Type:Run Capacitor
High MFD: 156.0	High MFD: 0.0
Usage Description: Start Capacitor	Usage Description: Run Capacitor
Volts: 330	Volts: 370
Run Capacitor	
Part No: 014-0064-12	
Low MFD: 30.0	
Type:Run Capacitor	
High MFD: 0.0	
Usage Description: Run Capacitor	
Volts: 440	

Nomenclature

CR22K6E-PFJ

Family Series

C: CR Compressors

Application Range

R: R-22/ High Temp. A/C & Heat Pump

Capacity

22K: Capacity

Model Variation

6: Model Variation - 6

Oil Type

E: Polyol Ester

Motor Type

P: 1 Phase/Capacitor Run, Permanent Split Capacitor

Motor Protection

F: Internal Inherent Protection

Voltage

J: 60Hz (265-1) 50Hz (200/240-1)

Miscellaneous

Alternate Application

Refrigerant	Freq	Phase	Voltage	Application
HFC R-404A	50	1 Ø	220/240 V	R1 HT
HFC R-407C	60	1 Ø	265 V	R1 AC
HFC R-407C	50	1 Ø	220/240 V	R1 AC

Nomenclature

[CR22K6E-PFJ](#)

Date	Data Group	Field	Old Data	New Data
No data available in table				