CR32K6E-PFJ

HCFC, R-22, 60 Hz, 1 - Phase, 265 V , Also Available with Variable Frequency Drives

Air Conditioning

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Summary

Performance		
Evaporator Temp. (°F)	45	45
Condensing Temp. (°F)	130	100
Return Gas Temp. (°F)	65	65
Liquid Temp. (°F)	115	85
Capacity (BTU/hr)	32000	42400
Power (W):	2970	2390
Current (Amps):	12.6	10.5
EER(BTU/Wh):	10.8	17.7
Mass Flow (lbs/hr):	469	545
Sound Data @		
Sound Power (dBA):	74 Avg	79 Max
Vibration mils(peak-peak):	3.4 Avg	4.4 Max
Record Date:		

Mechanical	
Displacement (in^3/Rev):	3.49
Displacement (ft^3/Hr):	
Overall Length (in):	10.23
Overall Width (in):	9.65
Overall Height (in):	13.81
Mounting Length (in):	7.50
Mounting Width (in):	7.50

Mounting Height (in):	14.19
Suction Size (in),Type:	3 / 4 Stub
Discharge Size (in),Type:	1 / 2 Stub
Initial Oil Charge (oz):	45
Oil Recharge (oz):	43
Net Weight (lbs):	66.0
Internal Free Volume (in^3):	
Horse Power:	

*Overall compressor height on Copeland Brand Product's specified mounting grommets.

Electrical

LRA High* (Amps):	83.0
LRA Low*(Amps):	
LRA Half Winding (Amps):	
MCC (Amps):	21
Max Operating Current (Amps):	
RLA, MCC/1.4(use for contactor selection)(Amps):	15.0
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	13.5
RPM:	
Box IP :	
UL File No:	
UL File Date:	1984-12-28

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Capacitors

Type	Part No	Low MFD	High MFD	Volts	User Description
Run Capacitor	014-0064-08	40.0	0.0	370	
Run Capacitor	014-0064-13	35.0	0.0	440	
Start Capacitor	014-0061-16	43.0	52.0	330	LOW TORQUE
Start Capacitor	014-0061-28	145.0	175.0	250	HIGH TORQUE

Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
R-407C HFC	265	1	60	Air Conditioning

Service Parts

Service Parts

Reference	Component	Quantity	Description	Comment
1	527-0044-00	1	SPACER-MOUNTING ASSM	
2	914-0036-04	1	CAP START KIT	
3	914-0037-17	1	RUN CAP KIT W/CLAMP	
4	940-0001-54	1	RELAY KIT	
10	918-0088-00	1	HEATER-CRANKCASE KIT	40/49W 240/265V FLEXIBLE
14	529-0060-24	1	POWER CABLE-MOLDED PLUG	
99	005-1210-00	1	COVER-TERMINAL BOX	

Accessories

Accessories

Category	Part Number	Description
(1) Variable Frequency Drive	EVM-322017-E20ENN	EVM, 3Ø, 200-240v, Output 200-240v@17A, Pro, IP20, Standard, No Options, Frame 2
(1) Variable Frequency Drive	EVM-122017-E20ENN	EVM, 1Ø, 200-240v, Output 200-240v@17A, Pro, IP20, Standard, No Options, Frame 2
(1) Variable Frequency Drive	EVM-322017-N20MNN	EVM, 3Ø, 200-240v, Output 200-240v@17A, Basic, IP20, Standard, No Options, Frame 2
(1) Variable Frequency Drive	EVM-322017-N20MFN	EVM, 3Ø, 200-240v, Output 200-240v@17A, Basic, IP20, With add on EMI filter, No Options, Frame 2
(1) Variable Frequency Drive	EVM-322017-E20EFN	EVM, 3Ø, 200-240v, Output 200-240v@17A, Pro, IP20, With add on EMI filter, No Options, Frame 2
(1) Variable Frequency Drive	EVM-122017-E20EFN	EVM, 1Ø, 200-240v, Output 200-240v@17A, Pro, IP20, With add on EMI filter, No Options, Frame 2
(1) Variable Frequency Drive	EVH-322017-R21BDN	EVH, 3Ø, 200-240v, Output 200-240v@17A, LCD Keypad, IP21, With 5% DC Link Choke, No Options, Frame 2
(1) Variable Frequency Drive	EVH-322017-R21BEN	EVH, 3Ø, 200-240v, Output 200-240v@17A, LCD Keypad, IP21, With 5% DC Link Choke + EMI Filter, No Options, Frame 2

Category	Part Number	Description
(1) Variable	EVH-322017-	EVH, 3Ø, 200-240v, Output 200-240v@17A, LCD Keypad, IP54, With 5% DC Link

Electrical Components

Electrical Components

Part No: 071-0508-51

Usage Description: Internal Protector

Vendor Part Number

15HM1783

Vendor Name

T I

Stator

Part No: 546-5081-12

Usage Description: Stator

Resistance: +/-7%

Start Wdg: 2.96

Run Wdg: 0.91

Potential

Part No: 040-0166-14

Usage Description: Potential Relay

Vendor Part Number

RVA4AL6D-918

Vendor Name

ELECTRICA

Start Capacitor

Part No: 014-0061-16

Low MFD: 43.0

Type:Start Capacitor

High MFD: 52.0

Usage Description: Start Capacitor

Volts: 330

Start Capacitor

Part No: 014-0061-28

Low MFD: 145.0

Type:Start Capacitor

High MFD: 175.0

Usage Description: Start Capacitor

Volts: 250

Run Capacitor

Part No: 014-0064-08

Low MFD: 40.0

Type:Run Capacitor

High MFD: 0.0

Usage Description: Run Capacitor

Volts: 370

Run Capacitor

Part No: 014-0064-13

Low MFD: 35.0

Type:Run Capacitor

High MFD: 0.0

Usage Description: Run Capacitor

Volts: 440

Nomenclature

CR32K6E-PFJ

Family Series

C: CR Compressors

Application Range

R: R-22/ High Temp. A/C & Heat Pump

Capacity

32K: Capacity

Model Variation

6: Model Variation - 6

Oil Type

E: Polyol Ester

Motor Type

P: 1 Phase/Capacitor Run, Permanent Split Capacitor

Motor Protection

F: Internal Inherent Protection

Voltage

J: 60Hz (265-1) 50Hz (200/240-1)

Miscellaneous

Alternate Application

Refrigerant	Freq	Phase	Voltage	Application
HFC R-407C	60	1 Ø	265 V	R1 AC
HFC R-407C	50	1 Ø	220/240 V	R1

Nomenclature

CR32K6E-PFJ

Date	Data Group	Field	Old Data	New Data
14-Jan-2014	Sound	Vibration Ave	1.5	3.4
14-Jan-2014	Sound	Vibration Max	2.5	4.4