

ZP38K5E-TFE

HFC, R-410A, 60 Hz, 3 - Phase, 575 V

Air Conditioning

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Summary

Performance		
Evaporator Temp. (°F)	45	50
Condensing Temp. (°F)	130	100
Return Gas Temp. (°F)	65	70
Liquid Temp. (°F)	115	85
Capacity (BTU/hr)	38100	51500
Power (W):	3630	2370
Current (Amps):	4.1	3
EER(BTU/Wh):	10.5	21.6
Mass Flow (lbs/hr):	560	630
Sound Data @ 45 / 130		
Sound Power (dBA):	68 Avg	73 Max
Vibration mils(peak-peak):	2.5 Avg	3.5 Max
Record Date:	2015-10-09	
Mechanical		
Displacement (in^3/Rev):	2.18	
Displacement (ft^3/Hr):		
Overall Length (in):	9.56	
Overall Width (in):	9.56	
Overall Height (in):	16.94	
Mounting Length (in):	7.50	
Mounting Width (in):	7.50	

Mounting Height (in):	17.17
Suction Size (in),Type:	7 / 8 Stub
Discharge Size (in),Type:	1 / 2 Stub
Initial Oil Charge (oz):	42
Oil Recharge (oz):	36
Net Weight (lbs):	66.9
Internal Free Volume (in^3):	209.5

Horse Power:

*Overall compressor height on Copeland Brand Product's specified mounting grommets.

Electrical

LRA High* (Amps):	33.0
LRA Low*(Amps):	
LRA Half Winding (Amps):	
MCC (Amps):	6.5
Max Operating Current (Amps):	6.0
RLA, MCC/1.4(use for contactor selection)(Amps):	4.6
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	4.2
RPM:	3500
Box IP :	21
UL File No:	SA-2337
UL File Date:	2003-12-17

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Capacitors

Type	Part No	Low MFD	High MFD	Volts	User Description
No data available in table					

Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
No data available in table				

Service Parts

Reference	Component	Quantity	Description	Comment
1	918-0041-00	1	HEATER-CRANKCASE	240V 40W WRAP AROUND
1	918-0041-01	1	HEATER-CRANKCASE	120V 40W WRAP AROUND
2	527-0116-00	1	SPACER-MOUNTING ASSM	
7	998-0510-98	1	VLV KIT 1/2"SWT/1-14UNC	DISCHARGE ROTALOCK
8	998-0510-90	1	VLV KIT 7/8"SWT / 11/4-12UNC	SUCTION ROTALOCK
9	998-7026-00	1	HEATER JUNCTION BOX KIT	
99	529-0060-24	1	POWER CABLE-MOLDED PLUG	
99	998-0034-02	1	SERV ADAPTOR KIT 7/8 STUB	SWEAT TO ROTALOCK ADAPTER KIT SUCTION
99	998-0034-08	1	ADPTR 11/4-12 TO 7/8 ID	ROTALOCK TO SWEAT ADAPTER KIT SUCTION
99	998-0034-15	1	SERV ADAPTOR KIT 1/2 STUB	SWEAT TO ROTALOCK ADAPTER KIT DISCHARGE

Accessories

Accessories

Category	Part Number	Description
CoreSense	571-0066-00	CoreSense™ Diagnostics Module (2 wire)
CoreSense	571-0066-01	CoreSense Diagnostics (Fixed Speed AC)
CoreSense	571-0067-00	CoreSense™ Diagnostics Module (3 wire)
CoreSense	571-0067-01	CoreSense Diagnostics (Fixed Speed HP)
CoreSense	571-0072-00	CoreSense Diagnostics (Two Stage UT)
Crankcase Heaters	018-0096-00	Crankcase Heater, 240V, 40W, 21.75" Lead Length
Crankcase Heaters	018-0096-01	Crankcase Heater, 120V, 40W, 21.75" Lead Length
Crankcase Heaters	018-0096-02	Crankcase Heater, 480V, 40W, 21.75" Lead Length
Crankcase Heaters	018-0096-03	Crankcase Heater, 575V, 40W, 21.75" Lead Length
Crankcase Heaters	018-0096-04	Crankcase Heater, 240V, 40W, 48.25" Lead Length

Electrical Components

Electrical Components	
Part No: 071-0613-00	Stator
Usage Description: Internal Protector	Part No: 546-2090-10
<u>Vendor Part Number</u>	Usage Description: Stator
34HM603	Resistance: +/-7%
<u>Vendor Name</u>	Start Wdg: 6.32
SENSATA	Run Wdg: 0.00

Nomenclature

ZP38K5E-TFE
Family Series
Z: Scroll
Application Range
P: A/C - R-410A/B
Capacity
38K: Capacity Multiplier-1000
Oil Type
E: Polyol Ester
Motor Type
T: 3 Phase
Motor Protection
F: Internal Inherent Protection
Voltage
E: 60Hz (575-3) 50Hz (-)

Miscellaneous

Alternate Application				
Refrigerant	Freq	Phase	Voltage	Application
No data available in table				
Nomenclature				
ZP38K5E-TFE				
Date	Data Group	Field	Old Data	New Data

Date	Data Group	Field	Old Data	New Data
26-Jun-2008	Rating	PubCode		Y
06-Jul-2007	Rating	PubCode		PRE
03-Oct-2008	2 Pt Perf	Cap Cond 2	46800	51500
03-Oct-2008	2 Pt Perf	EER Cond 2	19.5	21.6
03-Oct-2008	2 Pt Perf	MassFlow Cond 2	580	630