

ZPD154KCE-TE5

HFC, R-410A, 60 Hz, 3 - Phase, 200/230 V

Air Conditioning

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Summary

Performance		
Evaporator Temp. (°F)	45	35
Condensing Temp. (°F)	130	120
Return Gas Temp. (°F)	65	55
Liquid Temp. (°F)	115	105
Capacity (BTU/hr)	155000	138000
Power (W):	14100	12400
Current (Amps):	43.9	40.1
EER(BTU/Wh):	11	11.1
Mass Flow (lbs/hr):	2290	1930
Sound Data @		
Sound Power (dBA):	80 Avg	85 Max
Vibration mils(peak-peak):	3.0 Avg	4.5 Max
Record Date:	2016-06-27	
Mechanical		
Displacement (in^3/Rev):	8.72	
Displacement (ft^3/Hr):		
Overall Length (in):	12.94	
Overall Width (in):	11.73	
Overall Height (in):	22.21	
Mounting Length (in):	7.50	
Mounting Width (in):	7.50	

Mounting Height (in):	23.02
Suction Size (in),Type:	1 3 / 8 Stub
Discharge Size (in),Type:	7 / 8 Stub
Initial Oil Charge (oz):	114
Oil Recharge (oz):	110
Net Weight (lbs):	144.0
Internal Free Volume (in^3):	
Horse Power:	

*Overall compressor height on Copeland Brand Product's specified mounting grommets.

LRA High* (Amps):	300.0
LRA Low*(Amps):	
LRA Half Winding (Amps):	
MCC (Amps):	80
Max Operating Current (Amps):	59.0
RLA, MCC/1.4(use for contactor selection)(Amps):	57.1
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	51.3
RPM:	3500
Box IP :	54
UL File No:	SA-2337
UL File Date:	2007-02-07

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Capacitors

Type	Part No	Low MFD	High MFD	Volts	User Description
No data available in table					

Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
R-410A HFC	200/220	3	50	A/C, 50% Load Of Compressor Model
R-410A HFC	200/230	3	60	A/C, 50% Load Of Compressor Model
R-410A HFC	200/220	3	50	Air Conditioning

Service Parts

Service Parts				
Reference	Component	Quantity	Description	Comment
99	527-0210-00	1	MOUNTING SPACER ASSM	
99	910-0182-00	1	VALVE-SOLENOID	
99	910-0715-00	1	VALVE-OIL ADJUSTMENT 1/4FL X M9	
99	918-0047-00	1	HEATER-CRANKCASE	120V 90W WRAP AROUND
99	918-0047-01	1	HEATER-CRANKCASE	240V 90W WRAP AROUND
99	918-0047-02	1	HEATER-CRANKCASE	480V, 90W, WRAP AROUND
99	971-0064-05	1	KIT -115/240V MODULE	120/240V MODULE
99	971-0065-04	1	KIT 24 V MODULE	24V MODULE
99	985-0200-00	1	THERMISTOR KIT	
99	998-0010-00	1	SIGHTGLASS KIT	

Accessories

Accessories		
Category	Part Number	Description
Digital Components	543-0024-01	Digital Compressor Controller
Digital Components	998-0060-09	240V Digital Solenoid Coil

Electrical Components

Electrical Components
Part No: 571-0064-06
Usage Description: Modular Protector
<u>Vendor Part Number</u>
14800070
<u>Vendor Name</u>

WKK

Part No: 571-0065-05

Usage Description: Modular Protector

Vendor Part Number

14800170

Vendor Name

WKK

Stator

Part No: 046-0124-01

Usage Description: Stator

Resistance: +/-7%

Start Wdg: 0.23

Run Wdg: 0.00

Nomenclature

ZPD154KCE-TE5
Family Series
Z: Scroll
Application Range
P: A/C - R-410A/B
Modulation
D: Digital
Capacity
154K: Capacity Multiplier-1000
Oil Type
E: Polyol Ester
Motor Type
T: 3 Phase
Motor Protection
E: External Enhanced Protection
Voltage
5: 60Hz (200/230-3) 50Hz (200/220-3)

Miscellaneous

Alternate Application				
Refrigerant	Freq	Phase	Voltage	Application

Refrigerant	Freq	Phase	Voltage	Application
HFC R-410A	50	3 Ø	200/220 V	R1 A5
HFC R-410A	60	3 Ø	200/230 V	R1 A5
		Nomenclature		
		ZPD154KCE-TE5		
Date	Data Group	Field	Old Data	New Data
18-Mar-2014	Sound	Sound Ave		80
18-Mar-2014	Sound	Sound Max		85
18-Mar-2014	Sound	Sound Start		85
18-Mar-2014	Sound	Sound Start Max		93
18-Mar-2014	Sound	Sound Stop		82
18-Mar-2014	Sound	Sound Stop Max		90
18-Mar-2014	Sound	Vibration Ave		3
18-Mar-2014	Sound	Vibration Max		4.5
28-Jun-2016	2 Pt Perf	Amp Cond 2	35.1	40.1
28-Jun-2016	2 Pt Perf	Cap Cond 2	190000	138000