# ZR61K3E-PFV

HFC, R-407C, 60 Hz, 1 - Phase, 208/230 V

#### Air Conditioning

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

## Summary

Performance			
Evaporator Temp. (°F)	45	45	
Condensing Temp. (°F)	130	100	
Return Gas Temp. (°F)	65	65	
Liquid Temp. (°F)	115	85	
Capacity (BTU/hr)	59400	71700	
Power (W):	5620	3740	
Current (Amps):	26.2	18.3	
EER(BTU/Wh):	10.55	19.2	
Mass Flow (lbs/hr):	859	885	
Sound Data @			
Sound Power (dBA):	74 Avg	79 Max	
Vibration mils(peak-peak):	2.0 Avg	3.0 Max	
Record Date:	2014-08-07		
	Mechanical		
Displacement (in^3/Rev): 5.04			

Displacement (in^3/Rev):	5.04
Displacement (ft^3/Hr):	
Overall Length (in):	9.69
Overall Width (in):	9.69
Overall Height (in):	17.75
Mounting Length (in):	7.50
Mounting Width (in):	7.50

Mounting Height (in):	18.00				
Suction Size (in),Type:	7 / 8 Stub				
Discharge Size (in),Type:	1 / 2 Stub				
Initial Oil Charge (oz):	56				
Oil Recharge (oz):	52				
Net Weight (lbs):	90.0				
Internal Free Volume (in^3):	215				
Horse Power:	5.0				
*Overall compressor height on Co	opeland Brand Pr	oduct's s <b>Elecifie</b>	<b>h</b> mounting gror	nmets.	
LRA High* (Amps):			148.0		
LRA Low*(Amps):					
LRA Half Winding (Amps):					
MCC (Amps):		45			
Max Operating Current (Amp	s):		40.0		
RLA, MCC/1.4(use for contact	tor selection)(An	nps):	32.1		
RLA, MCC/1.4(use for contact RLA, MCC/1.56(use for break					
RLA, MCC/1.56(use for break			28.8		
RLA, MCC/1.56(use for break			28.8 3500		
RLA, MCC/1.56(use for break RPM: Box IP :			28.8 3500		
RLA, MCC/1.56(use for break RPM: Box IP : UL File No:	er & wire size se	lection)(Amps):	28.8 3500 21 1993-07-26	tor is approved	I.
RLA, MCC/1.56(use for break RPM: Box IP : UL File No: UL File Date:	er & wire size se	lection)(Amps):	28.8 3500 21 1993-07-26 or which the mo	tor is approved	L.
RLA, MCC/1.56(use for break RPM: Box IP : UL File No: UL File Date:	er & wire size se	lection)(Amps):	28.8 3500 21 1993-07-26 or which the mo	tor is approved	User Description
RLA, MCC/1.56(use for break RPM: Box IP : UL File No: UL File Date: *Low and High refer to the low an	<b>er &amp; wire size se</b>	lection)(Amps): voltage ranges fo Capacito	28.8 3500 21 1993-07-26 or which the mo		
RLA, MCC/1.56(use for break         RPM:         Box IP :         UL File No:         UL File Date:         *Low and High refer to the low at         Type         Part No	er & wire size sel	lection)(Amps): voltage ranges fo Capacito Low MFD	28.8 3500 21 1993-07-26 or which the mo	Volts	User Description SPECIAL CUSTOMER
RLA, MCC/1.56(use for break         RPM:         Box IP :         UL File No:         UL File Date:         *Low and High refer to the low at         Type         Part No         Run Capacitor       014-004	er & wire size sel nd high nominal v 1-01 4-38	lection)(Amps): /oltage ranges fo Capacito Low MFD 80.0	28.8 3500 21 1993-07-26 or which the mo	<b>Volts</b> 370	User Description User Description SPECIAL CUSTOMER APPLICATION PLASTIC CASE ALT ASIAN

**Alternate Applications** 

Phase

Refrigerant

Voltage

Frequency

Application

Refrigerant	Voltage	Phase	Frequency	Application	

#### Service Parts

eference	Component 918-0043-00 918-0043-01	<b>Quantity</b> 1	Description HEATER-CRANKCASE	Comment
		1	HEATER-CRANKCASE	
	010 0042 01			240V 70W WRAP AROUND
	910-0043-01	1	HEATER-CRANKCASE	480V 70W WRAP AROUND
	527-0116-00	1	SPACER-MOUNTING ASSM	
	914-0037-38	1	RUN CAP KIT	
	914-0006-10	1	CAP START KIT	
	940-0001-79	1	RELAY-POTENTIAL KIT	

#### Accessories

Accessories			
Category	Part Number	Description	
Crankcase Heaters	018-0095-00	Crankcase Heater, 240V, 70W, 21" Lead Length	
Crankcase Heaters	918-0043-07	Crankcase Heater Kit, 120V, 70W, Wrap Around, 48" Lead Length	
Crankcase Heaters	918-0043-02	Crankcase Heater Kit, 575V, 70W, Wrap Around, 48" Lead Length	
Crankcase Heaters	918-0043-01	Crankcase Heater Kit, 480V, 70W, Wrap Around, 48" Lead Length	
Crankcase Heaters	918-0043-00	Crankcase Heater Kit, 240V, 70W, Wrap Around, 48" Lead Length	
Crankcase Heaters	018-0095-09	Crankcase Heater, 277V, 70W, 21" Lead Length	
Crankcase Heaters	018-0095-08	Crankcase Heater, 400V, 70W, 48" Lead Length	
Crankcase Heaters	018-0095-07	Crankcase Heater, 120V, 70W, 48" Lead Length	

Category	Part Number	Description
Crankcase	018-0095-06	Crankcase Heater, 575V, 70W, 48" Lead Length

## **Electrical Components**

	Electrical Components
Part No: 071-0510-12	
Usage Description: Internal Protector	
<u>Vendor Part Number</u>	
16HM166	
Vendor Name	
Т. І.	
Part No: 071-0707-01	Stator
Usage Description: Internal Protector	Part No: 546-5078-48
Vendor Part Number	Usage Description: Stator
UP16NY0510-AO	Resistance: +/-7%
Vendor Name	Start Wdg: 0.65
UBUKATA	Run Wdg: 0.36
Stator	Potential
Part No: 846-5078-48	Part No: 040-0166-37
Usage Description: Stator	Usage Description: Potential Relay
Resistance: +/-7%	Vendor Part Number
Start Wdg: 0.65	RVA2AE6D-946
Run Wdg: 0.36	Vendor Name
	ELECTRICA
Start Capacitor	Run Capacitor
Part No: 014-0006-15	Part No: 014-0041-01
Low MFD: 270.0	Low MFD: 80.0
Type:Start Capacitor	Type:Run Capacitor
High MFD: 324.0	High MFD: 0.0
Usage Description: Start Capacitor	Usage Description: Run Capacitor
Volts: 330	Volts: 370
Run Capacitor	Run Capacitor
Part No: 014-0054-38	Part No: 014-0064-27
Low MFD: 80.0	Low MFD: 80.0

Type:Run Capacitor	Type:Run Capacitor
High MFD: 0.0	High MFD: 0.0
Usage Description: Run Capacitor	Usage Description: Run Capacitor
Volts: 370	Volts: 370

### Nomenclature

Family Series		
Z: Scroll		
Application Range		
<b>R:</b> A/C - R-22/407C/134a		
Capacity		
61K: Capacity Multiplier-1000		
Oil Type		
E: Polyol Ester		
Motor Type		
P: 1 Phase/Capacitor Run, Permanent Spli	it Capacitor	
Motor Protection		
F: Internal Inherent Protection		
Voltage		
<b>V:</b> 60Hz (208/230-1) 50Hz (-)		

#### Miscellaneous

Alternate Application				
Refrigerant	Freq	Phase	Voltage	Application
HCFC R-22	60	1 Ø	208/230 V	R1
		Nomenc	lature	
		<u>ZR61K3</u>	<u>E-PFV</u>	
Date	Data Group	Field	Old Data	New Data
07-Aug-2014	RatingRefNo	RatingRefNo	09-377	14-306
29-Jun-2009	RatingRefNo	RatingRefNo	09-209	09-377
29-Mar-2009	RatingRefNo	RatingRefNo	08-46	09-209
29-Jun-2009	Rating	PubCode		Y
07-Aug-2014	2 Pt Perf	Amp Cond 1	25.5	26.2

Date	Data Group	Field	Old Data	New Data
07-Aug-2014	2 Pt Perf	Amp Cond 2	17.6	18.3
07-Aug-2014	2 Pt Perf	Cap Cond 1	60000	59400
07-Aug-2014	2 Pt Perf	Cap Cond 2	73000	71700
07 Aug 2014	2 Dt Dorf	EED Cond 1	10.8	10 55