

ZP25K5E-TFD

HFC, R-410A, 60 Hz, 3 - Phase, 460 V [. Also Available with Variable Frequency Drives](#)

Air Conditioning

Production Status: Available for sale to all U.S. customers. Please check with your local Emerson Climate Technologies Representative for international availability.

Summary

Performance		
Evaporator Temp. (°F)	45	50
Condensing Temp. (°F)	130	100
Return Gas Temp. (°F)	65	70
Liquid Temp. (°F)	115	85
Capacity (BTU/hr)	25200	34400
Power (W):	2520	1645
Current (Amps):	3.75	2.75
EER(BTU/Wh):	10	20.9
Mass Flow (lbs/hr):	371	423
Sound Data @ 45 / 130		
Sound Power (dBA):	69 Avg	74 Max
Vibration mils(peak-peak):	2.0 Avg	3.0 Max
Record Date:	2017-03-01	
Mechanical		
Displacement (in^3/Rev):	1.46	
Displacement (ft^3/Hr):		
Overall Length (in):	9.56	
Overall Width (in):	9.56	
Overall Height (in):	12.27	
Mounting Length (in):	7.50	
Mounting Width (in):	7.50	

Mounting Height (in):	16.02
Suction Size (in),Type:	3 / 4 Stub
Discharge Size (in),Type:	1 / 2 Stub
Initial Oil Charge (oz):	25
Oil Recharge (oz):	21
Net Weight (lbs):	46.8
Internal Free Volume (in^3):	129.6

Horse Power:

*Overall compressor height on Copeland Brand Product's specified mounting grommets.

Electrical

LRA High* (Amps):	28.0
LRA Low*(Amps):	
LRA Half Winding (Amps):	
MCC (Amps):	6.5
Max Operating Current (Amps):	5.0
RLA, MCC/1.4(use for contactor selection)(Amps):	4.6
RLA, MCC/1.56(use for breaker & wire size selection)(Amps):	4.2
RPM:	3500
Box IP :	21
UL File No:	SA-2337
UL File Date:	2003-12-16

*Low and High refer to the low and high nominal voltage ranges for which the motor is approved.

Capacitors

Type	Part No	Low MFD	High MFD	Volts	User Description
No data available in table					

Alternate Applications

Refrigerant	Voltage	Phase	Frequency	Application
R-410A HFC	380/420	3	50	Air Conditioning

Service Parts

Reference	Component	Quantity	Description	Comment
1	918-0052-00	1	CRANKCASE HEATER KIT	240V 40W WRAP AROUND
1	918-0052-01	1	CRANKCASE HEATER KIT	120V 40W WRAP AROUND
2	527-0044-15	1	SPACER - MOUNTING ASSM	
7	998-0510-38	1	VLV KIT 3/4"SWT/1 1/4-12UNC	SUCTION ROTALOCK
7	998-0510-98	1	VLV KIT 1/2"SWT/1-14UNC	DISCHARGE ROTALOCK
99	529-0060-24	1	POWER CABLE-MOLDED PLUG	
99	998-0034-01	1	ADAP KIT 3/4"SWT / 1 1/4 RL	SWEAT TO ROTALOCK ADAPTER KIT SUCTION
99	998-0034-07	1	ADAP KIT 1 1/4 RL / 3/4"SWT	ROTALOCK TO SWEAT ADAPTER KIT SUCTION
99	998-0034-15	1	SERV ADAPTOR KIT 1/2 STUB	SWEAT TO ROTALOCK ADAPTER KIT DISCHARGE
99	998-0034-18	1	ADAPTER 1-14 TO 1/2 ID	ROTALOCK TO SWEAT ADAPTER KIT DISCHARGE

Accessories

Accessories

Category	Part Number	Description
(1) Variable Frequency Drive	EVM-3445D6- E20ENN	EVM, 3Ø, 380-480v, Output 380-480v@5.6A, Pro, IP20, Standard, No Options, Frame 1
(1) Variable Frequency Drive	EVM-3445D6- N20MNN	EVM, 3Ø, 380-480v, Output 380-480v@5.6A, Basic, IP20, Standard, No Options, Frame 1
(1) Variable Frequency Drive	EVM-3445D6- N20MFN	EVM, 3Ø, 380-480v, Output 380-480v@5.6A, Basic, IP20, With add on EMI filter, No Options, Frame 1
(1) Variable Frequency Drive	EVM-3445D6- E20EFN	EVM, 3Ø, 380-480v, Output 380-480v@5.6A, Pro, IP20, With add on EMI filter, No Options, Frame 1
(1) Variable Frequency Drive	EVH-3445D6- R21BDN	EVH, 3Ø, 380-480v, Output 380-480v@5.6A, LCD Keypad, IP21, With 5% DC Link Choke, No Options, Frame 1
(1) Variable Frequency Drive	EVH-3445D6- R21BEN	EVH, 3Ø, 380-480v, Output 380-480v@5.6A, LCD Keypad, IP21, With 5% DC Link Choke + EMI Filter, No Options, Frame 1
(1) Variable Frequency Drive	EVH-3445D6- R54BDN	EVH, 3Ø, 380-480v, Output 380-480v@5.6A, LCD Keypad, IP54, With 5% DC Link Choke, No Options, Frame 1

Category	Part Number	Description
(1) Variable Frequency Drive	EVH-3445D6-R54BEN	EVH, 3Ø, 380-480v, Output 380-480v@5.6A, LCD Keypad, IP54, With 5% DC Link Choke + EMI Filter, No Options, Frame 1
CoreSense	571-0072-00	CoreSense Diagnostics (Two Stage UT)

Electrical Components

Electrical Components
Part No: 071-0572-08
Usage Description: Internal Protector
<u>Vendor Part Number</u>
UP18GY202-780
<u>Vendor Name</u>
UBUKATA
Part No: 071-0572-40
Usage Description: Internal Protector
<u>Vendor Part Number</u>
UP18HY232-88C
<u>Vendor Name</u>
UBUKATA

Nomenclature

ZP25K5E-TFD
Family Series
Z: Scroll
Application Range
P: A/C - R-410A/B
Capacity
25K: Capacity Multiplier-1000
Oil Type
E: Polyol Ester
Motor Type
T: 3 Phase
Motor Protection
F: Internal Inherent Protection
Voltage
D: 60Hz (460-3) 50Hz (380/420-3)

Miscellaneous

Alternate Application				
Refrigerant	Freq	Phase	Voltage	Application
HFC R-410A	50	3 Ø	380/420 V	R1 AC
Nomenclature				
ZP25K5E-TFD				
Date	Data Group	Field	Old Data	New Data
20-Mar-2008	Status	Status	P	A
08-Feb-2008	RatingRefNo	RatingRefNo	06-936	08-23
17-Mar-2008	Rating	PubCode		Y
08-Apr-2005	Rating	PubCode		PRE
10-Sep-2008	Mech	Mech Spec No	MS91-Z1114	MS91-Z1272
11-Dec-2012	2 Pt Perf	MassFlow Cond 1	372	371
03-Oct-2008	2 Pt Perf	Cap Cond 2	31300	34400
03-Oct-2008	2 Pt Perf	EER Cond 2	18.85	20.9
03-Oct-2008	2 Pt Perf	MassFlow Cond 2	387	423

Date	Data Group	Field	Old Data	New Data
------	------------	-------	----------	----------