

AZURE[®]

Digi-Motor[®]

Installation Instructions

For 10865 & 10866 Motors

Technical Assistance 800-678-9888 • M-F 8AM - 5PM EST.



WARNING!

To prevent electric shock, personal injury, or death, turn off the electric power at the disconnect or main service panel prior to making any electrical connections.

Connections:

| | |
|-------------------|--|
| Red Jumper: | Voltage |
| White Jumper: | Rotation |
| Brown/White Plug: | For Optional Hand Held Tuner (MARS No. 08502) |
| White: | Neutral / L2 |
| Green/Yellow: | Ground |
| Multi Color: | (5) 115V Speed/Torque Taps |

Suggested Tap Selections:

| Tap | No. 10865 1/3 - 1/2 HP | No. 10866 3/4 - 1 HP |
|------------|------------------------|----------------------|
| 1 Low | Constant Fan | Constant Fan |
| 2 Med Low | 1/3 HP Heat | 3/4 HP Heat |
| 3 Med | 1/3 HP Cool | 3/4 HP Cool |
| 4 Med High | 1/2 HP Heat | 1 HP Heat |
| 5 High | 1/2 HP Cool | 1 HP Cool |

Connection Notes:

The Azure motor has 5 speed/torque taps. The table above offers suggested tap selections. Due to a variety of variables, these selections may need to be altered either higher or lower. Use MARS No. 08502 hand held tuner to manually adjust any of the speed/torque taps for optimum CFM flexibility especially in multi-speed applications (MARS No. 08502 is required).

98694 12/17

©2017 MOTORS & ARMATURES, Inc.
All rights reserved. MARS is a registered
trademark of Motors & Armatures, Inc.

www.marsdelivers.com

MARS[®]
Delivering Confidence