

## HUMIDIFIER TREATMENT

- Designed for humidifiers using up to 25 gallons per day.
- Equipped with 1/4 FPT Threads for easy installation and seasonal change-outs.
- Can be installed vertically or horizontally.
- Inhibits scale for one season.
- Not to be used on hot water lines. Usage temps of 40°-80°F.
- Includes two 1/4" compression fittings (pictured below)

### Description

Keep humidifiers clean and scale free with Humidi-Pro. Inhibits scale for one season. Install on the water line that supplies water directly to the humidifier.

### Application

- Clean pad or install new pad before installing Humidi-Pro.
- For best results humidifier should have a daily dump of water from the sump to diminish scale forming minerals.
- Install a new Humidi-Pro before each heating season.

### Installation Steps

1. Shut off water.
2. Disconnect existing filter or cut water line where filter is to be installed.
3. Install using 1/4" compression fittings (included) and thread seal tape.
4. Insure proper direction of water flow and connect inlet and outlet.
5. Carefully turn on the water and check for leaks.
6. Check the filter after approximately 8 hours for slight leaks not visible during initial installation.


## Water Treatment Products

### Humidi-Pro



1/4" MPT x 1/4" compression fittings

### Typical Installation Diagram



### Packaging

1 each      **4190-02**

Read and understand the product's label and Safety Data Sheet ("SDS") for precautionary and first aid information.

The SDS is available on the Nu-Calgon website at [www.nucalgon.com](http://www.nucalgon.com).

