RECTORSEAL

A CSW Industrials Company

PRODUCT DATA SHEET

# LINESHOT™

AC Drain Line Flush Device

## Description

Lineshot is a A/C drain line flush use to clean condensate drain lines fast. The Lineshot Device features a tapered fitting that is compatible with 3/8" – 3/4" drain openings along with a flexible hose for easy maneuverability. The product is lightweight and portable, which helps the technician save time on service calls and eliminates the need to haul heavy tanks into the attic. This product is compatible with the All-Access AA1 Cleanout Device.



## Directions

**RectorSeal Lineshot AC Drain Line Flush Device can be used individually or with RectorSeal All-Access® AA1 Cleanout Device.**

### When using the device directly on pipes ranging from 3/8"-3/4"

1. Ensure red safety lock is on (pushed up)
2. Unscrew the body of the device, and insert RectorSeal Lineshot $CO_2$ Cartridge (sold separately) with narrow end facing up
3. Carefully screw the body into the head of the device, ensuring that the cartridge is properly punctured NOTE: Completely screw-in the unit to prevent leaking gas
4. Push the red safety catch down
5. Place the end of hose with black nozzle at the desired location
6. Press the trigger to discharge the $CO_2$ to clear the clogged area

### When using the device with All-Access AA1 Cleanout Device

1. Ensure red safety lock is on (pushed up)
2. Unscrew the body of the device, and insert RectorSeal Lineshot $CO_2$ Cartridge with narrow end facing up
3. Carefully screw the body into the head of the device, ensuring that the cartridge is properly punctured NOTE: Completely screw-in the unit to prevent leaking gas
4. Insert the tapered nozzle into the All Access adapter OR insert the hose fitting into the Schrader valve
5. Push the red safety catch down
6. Press the trigger to discharge the $CO_2$ through All-Access AA1 Cleanout Device

## Characteristics | Features

- Lightweight
- Portable
- Environmentally-Friendly

## Packaging

| Code | Size | Qty. per Case | Lbs. per Case | Cubic Feet |
|---|---|---|---|---|
| 81980 | AC Drain Line Flush Device | 6 | 6 | 0.18 |
| 81981 | $CO_2$ Refill Cartridges | 6 | 8 | 0.16 |



**WARNING!**

**CARBON DIOXIDE 100%, 124-38-9. CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED. MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION. MAY INCREASE RESPIRATION AND HEART RATE. PROTECT FROM SUNLIGHT. STORE IN WELL VENTILATED PLACE.**

**FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT, CALL CHEMTREC-DAY OR NIGHT 1-800-424-9300.**

Do not open Lineshot until cartridge is empty or injury may occur. Completely discharge cartridge before opening. Do not discharge towards face or body. **KEEP OUT OF REACH OF CHILDREN. FOR CONDENSATE DRAIN LINE CLEANING ONLY.**

## Limited Warranty

RectorSeal, LLC makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RectorSeal, LLC. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal, LLC shall not be liable for incidental or consequential damages.

**RectorSeal, LLC • 2601 Spenwick Drive, Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • rectorseal.com**

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensor's and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2019 RectorSeal. All rights reserved. R50420-0719

Made In China