TECHNICAL bulletin

DP 88

SPRAY EDGE COATING

DP 88 is an aerosol spray edge coating or "duct butter" designed to quickly and conveniently coat the edges of fiberglass insulation. DP 88 is also used to repair and reface damaged fiberglass insulation. DP 88 is tack-free and flexible.

Recommended Uses:

- May be used to “butter” or encapsulate cut edges of fiberglass insulation.
- May be used to repair facing of new or existing fiberglass insulation.
- May be used to repair or reface fiberglass insulation and effectively control fiberglass erosion.
- May be used on internally lined ductwork and rigid fiberglass ductwork.

Features and Benefits:

- Convenient / Easy Application
- Tack-Free After Curing
- Quick Drying
- Ideal for Remediation Use
- Ductboard and Duct Liner Use
- Encapsulates Cut / Damaged Fiberglass
- Flexible
- Durable
- VOC Compliant / CARB Compliant

Directions For Use:

Surface Preparation: Surfaces should be clean, dry and free of dirt, oil and any foreign matter.

Application: Use in well ventilated area. Shake can vigorously until ball rattles; continue shaking for 30 seconds before use. Always point spray tip away from yourself and others. For best performance, use this product at temperatures above 50°F. Hold spray can tip 3 to 8 inches from surface to be sprayed, always at a 90° angle to surface. Apply even coats, overlapping passes slightly to insure proper coverage. Keep can moving to avoid excessive build-up, puddling, or bubbles. Dries to touch in 3 to 5 minutes and fully cures in 30 minutes.

IMPORTANT: After use, invert can and spray until only gas comes out to clear valve and spray tip.

Clean Up: Mineral spirits

Technical Data:

Color: Black
Chemical Family: Synthetic rubber
Application Temperature: 50°F - 110°F
Service Temperature: 0°F to 200°F
Flammability: Extremely Flammable
Dry Time: Dries to touch in 3 to 5 minutes depending on humidity, temperature, substrate, and application thickness. Fully cures in 30 minutes.
Coverage: Typical application will yield up to 400 linear feet on 1 inch duct liner or 33 square feet per can.
Packaging: Net wt. 14 oz. cans supplied 12 cans per case.
Shelf Life: 1 Year

KEEP OUT OF REACH OF CHILDREN
CONSULT S.D.S. BEFORE USING

DESIGN POLYMERICS
3301 W. Segerstrom
Santa Ana, CA 92704
Toll Free 800.641.0808
Phone 714.432.0600
Fax 714.432.0660
www.designpoly.com

Rev: v19212