



A CSW Industrials Company

PRODUCT DATA SHEET

JIM™ PR-1L

PVC • CPVC Hi-Etch Primer

Description

Jim PR-1L is a high-etch primer for use on both PVC and CPVC pipe, tubing and socket-type fittings.

Jim PR-1L is purple. Max VOC per SCAQMD 1168/368A or BAAQMD Method 40: 550 g/L.

Instructions

1. Store between 40°F and 110°F and apply between 15°F and 120°F. Use below 40°F only with proper solvent cement and with extreme care. Protect from freezing.
2. Cut pipe end square and remove ragged edges and burrs. Clean fitting socket and pipe of dirt, grease and moisture, and check for proper fit. Apply PRIMER as noted below. Primer is not required on ENT pipe and fittings. While still wet, quickly begin solvent cement application.
3. Wear non-permeable gloves during application to avoid skin contact.
4. Apply PRIMER evenly and freely to socket and then to pipe end for length of socket depth using supplied dauber applicator. Then apply again to socket. For pipe greater than 2" diameter, use natural-bristle brush size to 1/2 pipe diameter. During each application step, keep dauber or brush wet and moving about 10 seconds.
5. Temperature and humidity conditions may require repeated applications to one or both surfaces to avoid drying. While still wet, quickly apply proper solvent cement and make up pipe joint in accordance with cement's instructions.

For additional technical information, call Toll Free 1-800-231-3345.

Applications

Jim PR-1L is specifically formulated for all PVC and CPVC pipe applications such as potable water, pressure pipes, conduit, sewers and drain, waste and vent (DWV).

For use on all sizes and classes in both schedule 40 and schedule 80.



Characteristics | Features

- NSF approved for potable water systems
- UPC (IAPMO) listed under File No. 4585
- Meets ASTM F656 Specifications
- Fast acting, hi-etch primer prepares the surfaces for superior bonding strength
- Jim PR-1L's purple color ensures easy visual check for complete coverage
- LEED Compliant

Packaging

Code	Size	Qty. per Case	Lbs. per Case	Cubic Ft per Case
55910	1/4 Pint Dauber top (118 ml)	24 Cans	9	.18
55912	1/2 Pint Dauber top (237 ml)	24 Cans	15	.45
55914	Pint Dauber top (473 ml)	12 Cans	14	.43
55918	Quart Dauber top (946 ml)	12 Cans	26	.78
55920	Gallon can (3.8 L)	4 Cans	32	.80

Specifications

Wt/Gal @ 77°F	6.9 + .2 lbs./gal.
Flash Point	-20°C (-4°F) TCC based on Acetone
Color	Purple
Shelf Life	3 years



FILE NO. 4585



pw-dwv-sw

Suggestions and recommendations covering the use of our products are based on our past experience and laboratory findings. However, as we have no control as to the methods and conditions of application, we only assume responsibility for the uniformity of our products within manufacturing tolerances.



DANGER!

Highly flammable liquid and vapor. Harmful if swallowed. May be fatal if swallowed and enters airways. Causes skin irritation. Causes serious eye irritation. May cause respiratory irritation. May cause drowsiness or dizziness. Contains a chemical classified by the US EPA as a suspected possible carcinogen.

FOR CHEMICAL EMERGENCY, SPILL, LEAK, FIRE, EXPOSURE OR ACCIDENT, CALL CHEMTREC-DAY OR NIGHT 1-800-424-9300.

KEEP OUT OF REACH OF CHILDREN.

For additional information, refer to Safety Data Sheet (SDS).

Limited Warranty

RectorSeal, LLC makes the Limited Express Warranty that when the instructions for storage and handling of our products are followed we warrant our products to be free from defects. THIS LIMITED EXPRESS WARRANTY IS EXPRESSLY IN LIEU OF ANY OTHER EXPRESS OR IMPLIED WARRANTIES, INCLUDING ANY IMPLIED WARRANTY OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, AND OF ANY OTHER OBLIGATION ON THE PART OF RectorSeal, LLC. The sole remedy for breach of the Limited Express Warranty shall be the refund of the purchase price. All other liability is negated and disclaimed, and RectorSeal, LLC shall not be liable for incidental or consequential damages.

Manufactured by

RectorSeal, LLC

2601 Spenwick Drive • Houston, TX 77055, USA • 800-231-3345 • Fax 800-441-0051 • rectorseal.com

A CSW Industrials Company. RectorSeal, the logos and other trademarks are property of RectorSeal, LLC, its affiliates or its licensor's and are protected by copyright, trademark and other intellectual property laws, and may not be used without permission. RectorSeal reserves the right to change specifications without prior notice. ©2021 RectorSeal. All rights reserved. R50099-0921