PW 100

Shurtape®
TRUE TO YOUR WORK®

CORROSION-RESISTANT PVC PIPE WRAP TAPE

TYPICAL APPLICATIONS

- For corrosion protection of under and above ground metal and plastic pipe installations

PRODUCT FEATURES

- Resists corrosion, moisture, bacteria, fungus and abrasion
- UV-resistant
- Lead free
- Excellent conformability

CONSTRUCTION

Overall Grade/Function: General Purpose
Backing: 10 mil, PVC film
Adhesive: Non-corrosive, rubber-based

STANDARD WIDTH(S)

2 in

STANDARD LENGTH(S)

33.3 yd
Contact your Shurtape sales representative for other available sizes

STANDARD CORE SIZE

3 in

STORAGE AND USAGE CONDITIONS

Tape should be stored in its original packaging in a cool, dry area away from direct sunlight and should be used within 12 months of date of shipment. Surfaces to which tape is applied should be clean, dry and free of grease, oil or other contaminants.

COLOR(S)

BLACK PRINTED (BPT)

BLACK (BLK)

PHYSICAL PROPERTIES	STANDARD	METRIC
Tensile Strength	25 lbs/in width	44.0 N/10 mm
Adhesion to Stainless Steel	20 oz/in width	2.19 N/10 mm
Thickness	10 mils	0.25 mm
Elongation	200%	200%
Dielectric Strength	600 volts/mil	600 volts/mil
Application Temperature Range	14 F to 176 F	-10 C to 80 C

Physical and performance characteristics shown above are obtained from tests recommended by PSTC, ASTM, government agencies or Shurtape Technologies, LLC, Quality Assurance and Technical Service departments and do not represent a guarantee of product performance. Individual rolls may vary slightly from these averages. The user should determine whether the product is fit for a particular purpose and is suitable for the user's method of application before use.



Shurtape Technologies, LLC | PO BOX 1530 Hickory, NC 28603-1530 USA | Phone 1.888.442.TAPE (8273) | Fax 800.335.7651 | shurtape.com

ISO 9001 CERTIFIED QUALITY SYSTEM

Shurtape® is a registered trademark of Shurtape Technologies, LLC Form# TDS-PW-100-11/18/2021