10 x 38mm MIDGET FUSES

KLK Series
Fast-Acting Fuse
600 Vac

AMPERE RATINGS			
1/10	1	5	15
1/8	1 1/2	6	20
2/10	2	7	25
1/4	2 1/2	8	30
3/10	3	9	—
1/2	3 1/2	10	—
3/4	4	12	—

Specifications

Fast-acting, high-interrupting capacity fuse designed for control circuits, HID lighting, street-lighting, meter circuits.

Voltage Ratings 600 Vac
500 Vdc

Interrupting Ratings 100 kA @ 600 Vac
50 kA @ 500 Vdc
(capable of 200 kA)

Approvals UL Listed (E10480)
CSA Certified (LR29862)

Dimensions **L** 38.1mm (1 1/2")
D 10.31mm (13/32")

littelfuse.com/klk

KLKD Series
Fast-Acting Fuse
600 Vac/dc

AMPERE RATINGS			
1/10	1	5	15
1/8	1 1/2	6	20
2/10	2	7	25
1/4	2 1/2	8	30
3/10	3	9	—
1/2	3 1/2	10	—
3/4	4	12	—

Specifications

Fast-acting, high DC rated fuse used in solar combiner boxes, DC control circuits, UPS protection. Available in PC board mount.

Voltage Ratings 600 Vac/dc

Interrupting Ratings 100 kA @ 600 Vac
10 kA @ 600 Vdc (UL 248-19)
50 kA @ 600 Vdc (UL 248-14)
(capable of 200 kA)

Approvals UL Listed (E339112 & E10480)
CSA Certified (LR29862)

Dimensions **L** 38.1mm (1 1/2")
D 10.31mm (13/32")

littelfuse.com/klkd

FLM Series
Time-Delay Fuse
250 Vac

AMPERE RATINGS				
1/10	8/10	2	4 1/2	10
15/100	1	2 1/4	5	12
2/10	1 1/8	2 1/2	5 6/10	15
1/4	1 1/4	2 8/10	6	20
3/10	1 4/10	3	6 1/4	25
4/10	1 1/2	3 2/10	7	30
1/2	1 6/10	3 1/2	8	—
6/10	1 8/10	4	9	—

Specifications

250V time-delay fuses used to protect circuits with high in-rush. Especially suited for supplemental protection of small motors.

Voltage Ratings 250 Vac
125 Vdc self-certified @ 10 kA

Interrupting Ratings 10 kA @ 250 Vac

Approvals UL Listed (File: E10480)
CSA Certified (029862_0_000)

Dimensions **L** 38.1mm (1 1/2")
D 10.31mm (13/32")

littelfuse.com/flm

FLQ Series
Time-Delay Fuse
500 Vac

AMPERE RATINGS				
1/10	1/2	2	5	12
1/8	6/10	2 1/4	5 6/10	14
15/100	8/10	2 1/2	6	15
3/16	1	3	6 1/4	20
2/10	1 1/8	3 2/10	7	25
1/4	1 1/4	3 1/2	8	30
3/10	1 1/2	4	9	—
4/10	1 6/10	4 1/2	10	—

Specifications

500V time-delay fuses for supplemental protection of control power transformers, solenoids, and circuits with high in-rush. Ideal for 480 V systems.

Voltage Ratings 500 Vac
300 Vdc self-certified @ 10 kA

Interrupting Ratings 10 kA @ 500V ac

Approvals UL Listed (E10480)
CSA Certified (LR29862)

Dimensions **L** 38.1mm (1 1/2")
D 10.31mm (13/32")

littelfuse.com/flq

BLN Series
Fast-Acting Fuse
250 Vac

AMPERE RATINGS				
1	3	6	12	25
1 1/2	4	8	15	30
2	5	10	20	—

Specifications

250 volt BLN fuses provide low-cost protection for military applications and control circuits.

Voltage Ratings 250 Vac

Interrupting Ratings 10 kA @ 250 Vac

Approvals UL Listed (E10480)
CSA Certified (LR29862)

Dimensions **L** 38.1mm (1 1/2")
D 10.31mm (13/32")

littelfuse.com/bln

BLF Series
Fast-Acting Fuse
125/250 Vac

AMPERE RATINGS			
1/2	3	7	15
1	4	8	20
1 1/2	5	9	25
2	6	10	30
2 1/2	6 1/4	12	—

Specifications

BLF fuses are the lowest price midget fuse. They are suitable for control circuit and instrument protection in dry locations.

Voltage Ratings 250 Vac 1/2 - 15 A
125 Vac 20 - 30 A

Interrupting Ratings 10 kA @ rated Vac

Approvals UL Listed (E10480)
CSA Certified (LR29862)

Dimensions **L** 38.1mm (1 1/2")
D 10.31mm (13/32")

littelfuse.com/blf

© 2018 Littelfuse POWR-GARD® Products Catalog