

Pull-out Disconnect Switches

Product

DiversiTech Pull-out Disconnect Switches: DDS-30, DDS-60 (fusible), DDS-60U and EDS-60U (non-fusible)

Application

HVAC circuitry

Power Rating

30A (DDS-30) or 60A at 240VAC, 10 horsepower max

Indoor/Outdoor

Indoor/Outdoor

Package Medium

Metal case with 180 degree opening door

Advantages

Convenient design allows for easy access to controls via wide-opening, reversible door with full dead front. Fused models benefit from having fuses located in easy pull-out handle with indicator lights for blown fuses. Line, load, and ground terminals aligned for easy wiring. EDS-60U Low-profile model also available for tighter spaces.

Directions

Please refer to an electronic copy of this product's brochure at www.diversitech.com/literature/lit-fly-disc.pdf

HAZMAT Hazard

None.

SKU Specific Package Metrics

UPC

DDS-30 - 095247082445

DDS-60 - 095247082452

DDS-60U - 095247082421

EDS-60U - 095247089420

Unit Dimensions

DDS-30 - 2-5/8"L x 5"W x 7-1/2"H

DDS-60 - 2-3/4"L x 5-1/8"W x 8-5/8"H

DDS-60U - 2-3/8"L x 5"W x 7-1/2"H

EDS-60U - 2-1/2"L x 4.8"W x 6.3"H

Unit Weight

DDS-30 - 2.7 lbs.

DDS-60 - 3.3 lbs.

DDS-60U - 2.5 lbs.

EDS-60U - N/A

Quantity per Package

10

Case Dimensions

DDS-30 - 14"L x 11"W x 8-1/4"H

DDS-60 - 16"L x 11"W x 9-1/4"H

DDS-60U - 13"L x 11"W x 8-1/4"H

EDS-60U - N/A

Case Weight

DDS-30 - 28.6 lbs.

DDS-60 - 33.7 lbs.

DDS-60U - 26.6 lbs.

EDS-60U - N/A

Accepts Fuse

DDS-30 - Two with 14.5 mm diam x 51.0 length

DDS-60 - Two with 20.5 mm x 76.5 mm length

DDS-60U - n/a

EDS-60U - n/a



DDS-30



DDS-60