ARCHITECTURAL SPECIFICATIONS PANASONIC ADVANCED VENTILATION SERIES

WhisperControl

FV-WCCS1-W (White)
FV-WCCS1-A (Light Almond)
Fan control mounts to wall and must include combination humidity and temperature sensor that anticipates dew point and automatically turns a vent fan on. Must include an adjustable Minutes Per Hour fan timer (0-60 mins) for compliance with ASHRAE 62.2 and a Moisture Sensitivity Selector to fine tune the wall control for a dry or moist environment. Automatic Fan Control - 30 minute countdown timer initiates after moisture returns to normal levels. Manual Fan Control - 20 minute countdown timer initiates once fan is turned on. Blue LED indicates fan is on. Commercial Grade - 8 Amp max load/120V. For indoor use. Includes matching wall plate. May be used to comply with ASHRAE 62.2, LEED, ENERGY STAR® 3.0 and CALGreen.

FV-WCCS2-W (White)
FV-WCCS2-A (Light Almond)
Fan and light control mounts to wall and must include a combination humidity and temperature sensor that anticipates dew point and automatically turns a vent fan on. Must include an adjustable Minutes Per Hour fan timer (0-60 mins) for compliance with ASHRAE 62.2 and a Moisture Sensitivity Selector to fine tune the wall control for a dry or moist environment. Automatic Fan Control - 30 minute countdown timer initiates after moisture returns to normal levels. Manual Fan Control - 20 minute countdown timer initiates once fan is turned on. Blue LED indicates fan is on. Commercial Grade - 8 Amp max load/120V. For indoor use. Includes matching wall plate. May be used to comply with ASHRAE 62.2, LEED, ENERGY STAR® 3.0 and CALGreen.

FV-WCD01-W (White)
FV-WCD01-A (Light Almond)
Fan control mounts to wall and must include a preset countdown timer for 5-15-30-45 or 60 minute intervals. Must include an Adjustable Minutes Per Hour fan timer (0-60 mins) for compliance with ASHRAE 62.2. Manual On/Off Fan Control, Blue LED indicates fan is on. Commercial Grade, 8 Amp max load/120 V. For indoor use. Includes matching wall plate. May be used to comply with ASHRAE 62.2, LEED and ENERGY STAR® 3.0.

FV-WCD02-W (White)
FV-WCD02-A (Light Almond)

Fan and light control mounts to wall and must include a preset countdown timer for 5-15-30-45 or 60 minute intervals. Must include an Adjustable Minutes Per Hour fan timer (0-60 mins) for compliance with ASHRAE 62.2. Manual On/Off Fan Control, Blue LED

indicates fan is on. Commercial Grade, 8 Amp max load/120 V. For indoor use. Includes matching wall plate. May be used to comply with ASHRAE 62.2, LEED and ENERGY STAR® 3.0.