## TILT-IN CABLE BOX CONNECTORS - STEEL



Connects Romex® Brand SIM*pull*® Type NM-B Cable or non-metallic sheathed cable to box or enclosure

**SPECIFICATIONS:**

- Material: Steel, Zinc Electroplated
- Notes: Locknut not required

| STOCK # | TRADE SIZE | INNER QTY | MASTER QTY |
|---|---|---|---|
| L-15 | 1/2" | 100 | 500 |
| L-16 | 3/4" | 50 | 250 |
| L-17 | 1-1/4" | 25 | 125 |
| L-18 | 1-1/2" | N/A | 25 |

## EZ-IN™ MINI-SPLIT CONNECTORS

64235201



64275801



**APPLICATION**

- Suitable for use with Ultra-Whip Wiring Assemblies
- Easy and hassle-free fitting hook-ups
- Commonly used for connecting air conditioners, pumps, motors, compressors, pool equipment and similar equipment
- Highly Flexible Non-metallic Conduit with Factory Installed Conductors Type B (LFNC-B) Fittings

**SPECIFICATIONS:**

The fittings meet UL Standard 514B, CSA Standard C22.2 No.18, and NEMA FB-1. Assemblies complies with NEC® Article 356, UL Standard 1660, and CSA Standard C22.2 No 227.2

| STOCK # | TYPE | HUB SIZE | RANGE OVER JACKET OD MIN-MAX | GROMMET COLOR | A LENGTH | B DIAMETER | C HEX | D LENGTH | BOX PACK |
|---|---|---|---|---|---|---|---|---|---|
| 64235201 | STRAIGHT CONNECTOR, 1/2" STEEL ZINC PLATED TECK50 | 1/2" | .610 - .720<br>.560 - .610<br>.485 - .585" | Black, Grey, Yellow | 1-31/32" | 1-3/16" | 1-1/8" | 19/32" | 25 |
| 64275801 | 90 DEGREE CONNECTOR TECK5090 | 1/2" | .610 - .720<br>.560 - .610<br>.485 - .585" | Black, Grey, Yellow | 3-1/2" | 2" | 1-1/8" | 19/32" | 15 |

## NONMETALLIC LIQUID-TIGHT BOX CONNECTORS STRAIGHT

c UL us LISTED



Connects liquid-tight nonmetallic conduit to box or enclosure

**SPECIFICATIONS:**

- Material: Nylon
- Features: Suitable for use with liquid-tight
- flexible non-metallic conduit, Type B
- Notes: S suffix denotes one-piece screw-in type

| STOCK # | TRADE SIZE | INNER QTY | MASTER QTY |
|---|---|---|---|
| NMLQ-1050 | 1/2" | 25 | 100 |
| NMLQ-1075 | 3/4" | 10 | 100 |
| NMLQ-1050-S | 1/2" | 25 | 100 |
| NMLQ-1075-S | 3/4" | 25 | 100 |