







NOTES:
- Extreme Temperature Durability (-40°F to 260°F).
- High Tensile Strength.
- Crack/Split/Leak/Rust Resistant.
- Self Extinguishing.
- Made With Pride in the USA

ENGINEERING	NAME	DATE
DRAWN BY ENG.	DS	7/21/09
CHECKED BY ENG.	JK	7/21/09
ENG APPR.	CC	7/21/09
MFG APPR.	CC	7/21/09

UNLESS OTHERWISE SPECIFIED:

DIMENSIONS ARE IN INCHES
TOLERANCES:
FRACTIONAL ±.032
ANGULAR: MACH ± .5 ° BEND ±2°
TWO PLACE DECIMAL ± .010
THREE PLACE DECIMAL ± .005

INTERPRET GEOMETRIC TOLERANCING PER: ANSI Y14.5, 1994

PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF RECTORSEAL.
ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF RECTORSEAL IS PROHIBITED.

RECTORSEAL

2601 Spenwick Drive,
Houston, TX 77055
800-231-3345

TITLE:

AG-G 30x62 SPECIFICATIONS SHEET

SIZE	SCALE	SHEET
A	SCALE: 1:15	SHEET 1 OF 1